

```

1 <!--===== Imported Names =====>
2 <!ENTITY % ContentType "CDATA">
3 <!ENTITY % ContentTypes "CDATA">
4 <!ENTITY % Charset "CDATA">
5 <!ENTITY % Charsets "CDATA">
6 <!ENTITY % LanguageCode "NAME">
7 <!ENTITY % Character "CDATA">
8 <!ENTITY % LinkTypes "CDATA">
9 <!ENTITY % MediaDesc "CDATA">
10 <!ENTITY % URI "CDATA">
11 <!ENTITY % Datetime "CDATA">
12 <!ENTITY % Script "CDATA">
13 <!ENTITY % StyleSheet "CDATA">
14 <!ENTITY % Text "CDATA">
15
16 <!ENTITY % head.misc "SCRIPT|STYLE|META|LINK|OBJECT" -- repeatable head elements
-->
17 <!ENTITY % heading "H1|H2|H3|H4|H5|H6">
18 <!ENTITY % list "UL | OL">
19 <!ENTITY % preformatted "PRE">
20
21 <!--===== Character mnemonic entities =====>
22 <!ENTITY % HTMLat1 PUBLIC "-//W3C//ENTITIES Latin1/EN//HTML" "HTMLat1.ent">
23 %HTMLat1;
24 <!ENTITY % HTMLsymbol PUBLIC "-//W3C//ENTITIES Symbols/EN//HTML" "HTMLsymbol.en
t">
25 %HTMLsymbol;
26 <!ENTITY % HTMLspecial PUBLIC "-//W3C//ENTITIES Special/EN//HTML" "HTMLspecial.
ent">
27 %HTMLspecial;
28 <!--===== Generic Attributes =====>
29 <!ENTITY % coreattrs
30 "id ID #IMPLIED -- document-wide unique id --
31 class CDATA #IMPLIED -- space-separated list of classes --
32 style %StyleSheet; #IMPLIED -- associated style info --
33 title %Text; #IMPLIED -- advisory title --"
34 >
35 <!ENTITY % i18n
36 "lang %LanguageCode; #IMPLIED -- language code --
37 dir (ltr|rtl) #IMPLIED -- direction for weak/neutral text --"
38 >
39 <!ENTITY % events
40 "onclick %Script; #IMPLIED -- a pointer button was clicked --
41 ondblclick %Script; #IMPLIED -- a pointer button was double clicked--
42 onmousedown %Script; #IMPLIED -- a pointer button was pressed down --
43 onmouseup %Script; #IMPLIED -- a pointer button was released --
44 onmouseover %Script; #IMPLIED -- a pointer was moved onto --
45 onmousemove %Script; #IMPLIED -- a pointer was moved within --
46 onmouseout %Script; #IMPLIED -- a pointer was moved away --
47 onkeypress %Script; #IMPLIED -- a key was pressed and released --
48 onkeydown %Script; #IMPLIED -- a key was pressed down --
49 onkeyup %Script; #IMPLIED -- a key was released --"
50 >
51 <!ENTITY % attrs "%coreattrs; %i18n; %events;">
52 <!--===== Text Markup =====>
53 <!ENTITY % fontstyle "TT | I | B | BIG | SMALL">
54 <!ENTITY % phrase "EM | STRONG | DFN | CODE |
55 SAMP | KBD | VAR | CITE | ABBR | ACRONYM" >
56 <!ENTITY % special
57 "A | IMG | OBJECT | BR | SCRIPT | MAP | Q | SUB | SUP | SPAN | BDO">
58 <!ENTITY % formctrl "INPUT | SELECT | TEXTAREA | LABEL | BUTTON">
59 <!-- %inline; covers inline or "text-level" elements -->
60 <!ENTITY % inline "#PCDATA | %fontstyle; | %phrase; | %special; | %formctrl;">
61 <!ELEMENT (%fontstyle;|%phrase;) - - (%inline;)*>
62 <!ATTLIST (%fontstyle;|%phrase;)
63 %attrs; -- %coreattrs, %i18n, %events --

```

```

64 >
65 <!ELEMENT (SUB|SUP) - - (%inline;)* -- subscript, superscript -->
66 <!ATTLIST (SUB|SUP)
67 %attrs; -- %coreattrs, %i18n, %events --
68 >
69 <!ELEMENT SPAN - - (%inline;)* -- generic language/style container -->
70 <!ATTLIST SPAN
71 %attrs; -- %coreattrs, %i18n, %events --
72 %reserved; -- reserved for possible future use --
73 >
74 <!ELEMENT BDO - - (%inline;)* -- I18N BiDi over-ride -->
75 <!ATTLIST BDO
76 %coreattrs; -- id, class, style, title --
77 lang %LanguageCode; #IMPLIED -- language code --
78 dir (ltr|rtl) #REQUIRED -- directionality --
79 >
80 <!ELEMENT BR - O EMPTY -- forced line break -->
81 <!ATTLIST BR
82 %coreattrs; -- id, class, style, title --
83 >
84 <!--===== HTML content models =====>
85 <!ENTITY % block
86 "P | %heading; | %list; | %preformatted; | DL | DIV | NOSCRIPT |
87 BLOCKQUOTE | FORM | HR | TABLE | FIELDSET | ADDRESS">
88 <!ENTITY % flow "%block; | %inline;">
89 <!--===== Document Body =====>
90 <!ELEMENT BODY O O (%block;|SCRIPT)+ +(INS|DEL) -- document body -->
91 <!ATTLIST BODY
92 %attrs; -- %coreattrs, %i18n, %events --
93 onload %Script; #IMPLIED -- the document has been loaded --
94 onunload %Script; #IMPLIED -- the document has been removed --
95 >
96 <!ELEMENT ADDRESS - - (%inline;)* -- information on author -->
97 <!ATTLIST ADDRESS
98 %attrs; -- %coreattrs, %i18n, %events --
99 >
100 <!ELEMENT DIV - - (%flow;)* -- generic language/style container -->
101 <!ATTLIST DIV
102 %attrs; -- %coreattrs, %i18n, %events --
103 %reserved; -- reserved for possible future use --
104 >
105 <!--===== The Anchor Element =====>
106 <!ENTITY % Shape "(rect|circle|poly|default)">
107 <!ENTITY % Coords "CDATA" -- comma-separated list of lengths -->
108 <!ELEMENT A - - (%inline;)* -(A) -- anchor -->
109 <!ATTLIST A
110 %attrs; -- %coreattrs, %i18n, %events --
111 charset %Charset; #IMPLIED -- char encoding of linked resource --
112 type %ContentType; #IMPLIED -- advisory content type --
113 name CDATA #IMPLIED -- named link end --
114 href %URI; #IMPLIED -- URI for linked resource --
115 hreflang %LanguageCode; #IMPLIED -- language code --
116 rel %LinkTypes; #IMPLIED -- forward link types --
117 rev %LinkTypes; #IMPLIED -- reverse link types --
118 accesskey %Character; #IMPLIED -- accessibility key character --
119 shape %Shape; rect -- for use with client-side image maps --
120 coords %Coords; #IMPLIED -- for use with client-side image maps --
121 tabindex NUMBER #IMPLIED -- position in tabbing order --
122 onfocus %Script; #IMPLIED -- the element got the focus --
123 onblur %Script; #IMPLIED -- the element lost the focus --
124 >
125 <!--===== Client-side image maps =====>
126 <!ELEMENT MAP - - ((%block;)| AREA)+ -- client-side image map -->
127 <!ATTLIST MAP
128 %attrs; -- %coreattrs, %i18n, %events --
129 name CDATA #REQUIRED -- for reference by usemap --

```

```

130 >
131 <!ELEMENT AREA - O EMPTY -- client-side image map area -->
132 <!ATTLIST AREA
133 %attrs; -- %coreattrs, %il8n, %events --
134 shape %Shape; rect -- controls interpretation of coords --
135 coords %Coords; #IMPLIED -- comma-separated list of lengths --
136 href %URI; #IMPLIED -- URI for linked resource --
137 nohref (nohref) #IMPLIED -- this region has no action --
138 alt %Text; #REQUIRED -- short description --
139 tabindex NUMBER #IMPLIED -- position in tabbing order --
140 accesskey %Character; #IMPLIED -- accessibility key character --
141 onfocus %Script; #IMPLIED -- the element got the focus --
142 onblur %Script; #IMPLIED -- the element lost the focus --
143 >
144 <!------- The LINK Element ----->
145 <!ELEMENT LINK - O EMPTY -- a media-independent link -->
146 <!ATTLIST LINK
147 %attrs; -- %coreattrs, %il8n, %events --
148 charset %Charset; #IMPLIED -- char encoding of linked resource --
149 href %URI; #IMPLIED -- URI for linked resource --
150 hreflang %LanguageCode; #IMPLIED -- language code --
151 type %ContentType; #IMPLIED -- advisory content type --
152 rel %LinkTypes; #IMPLIED -- forward link types --
153 rev %LinkTypes; #IMPLIED -- reverse link types --
154 media %MediaDesc; #IMPLIED -- for rendering on these media --
155 >
156 <!------- Images ----->
157 <!ENTITY % Length "CDATA" -- nn for pixels or nn% for percentage length -->
158 <!ENTITY % MultiLength "CDATA" -- pixel, percentage, or relative -->
159 <!ENTITY % Pixels "CDATA" -- integer representing length in pixels -->
160 <!ELEMENT IMG - O EMPTY -- Embedded image -->
161 <!ATTLIST IMG
162 %attrs; -- %coreattrs, %il8n, %events --
163 src %URI; #REQUIRED -- URI of image to embed --
164 alt %Text; #REQUIRED -- short description --
165 longdesc %URI; #IMPLIED -- link to long description
166 (complements alt) --
167 name CDATA #IMPLIED -- name of image for scripting --
168 height %Length; #IMPLIED -- override height --
169 width %Length; #IMPLIED -- override width --
170 usemap %URI; #IMPLIED -- use client-side image map --
171 ismap (ismap) #IMPLIED -- use server-side image map --
172 >
173 <!------- OBJECT ----->
174 <!ELEMENT OBJECT - - (PARAM | %flow;)*
175 -- generic embedded object -->
176 <!ATTLIST OBJECT
177 %attrs; -- %coreattrs, %il8n, %events --
178 declare (declare) #IMPLIED -- declare but don't instantiate flag --
179 classid %URI; #IMPLIED -- identifies an implementation --
180 codebase %URI; #IMPLIED -- base URI for classid, data, archive--
181 data %URI; #IMPLIED -- reference to object's data --
182 type %ContentType; #IMPLIED -- content type for data --
183 codetype %ContentType; #IMPLIED -- content type for code --
184 archive CDATA #IMPLIED -- space-separated list of URIs --
185 standby %Text; #IMPLIED -- message to show while loading --
186 height %Length; #IMPLIED -- override height --
187 width %Length; #IMPLIED -- override width --
188 usemap %URI; #IMPLIED -- use client-side image map --
189 name CDATA #IMPLIED -- submit as part of form --
190 tabindex NUMBER #IMPLIED -- position in tabbing order --
191 %reserved; #IMPLIED -- reserved for possible future use --
192 >
193 <!ELEMENT PARAM - O EMPTY -- named property value -->
194 <!ATTLIST PARAM
195 id ID #IMPLIED -- document-wide unique id --

```

```

196 name CDATA #REQUIRED -- property name --
197 value CDATA #IMPLIED -- property value --
198 valuetype (DATA|REF|OBJECT) DATA -- How to interpret value --
199 type %ContentType; #IMPLIED -- content type for value
200 when valuetype=ref --
201 >
202 <!------- Horizontal Rule ----->
203 <!ELEMENT HR - O EMPTY -- horizontal rule -->
204 <!ATTLIST HR
205 %attrs; -- %coreattrs, %il8n, %events --
206 >
207 <!------- Paragraphs ----->
208 <!ELEMENT P - O (%inline;)* -- paragraph -->
209 <!ATTLIST P
210 %attrs; -- %coreattrs, %il8n, %events --
211 >
212 <!------- Headings ----->
213 <!ELEMENT (H1|H2|H3|H4|H5|H6) (%inline;)* -- heading -->
214 <!ATTLIST (H1|H2|H3|H4|H5|H6)
215 %attrs; -- %coreattrs, %il8n, %events --
216 >
217 <!------- Preformatted Text ----->
218 <!ENTITY % pre.exclusion "IMG|OBJECT|BIG|SMALL|SUB|SUP">
219 <!ELEMENT PRE - - (%inline;)* -(%pre.exclusion;) -- preformatted text -->
220 <!ATTLIST PRE
221 %attrs; -- %coreattrs, %il8n, %events --
222 >
223 <!------- Inline Quotes ----->
224 <!ELEMENT Q - - (%inline;)* -- short inline quotation -->
225 <!ATTLIST Q
226 %attrs; -- %coreattrs, %il8n, %events --
227 cite %URI; #IMPLIED -- URI for source document or msg --
228 >
229 <!------- Block-like Quotes ----->
230 <!ELEMENT BLOCKQUOTE - - (%block;|SCRIPT)+ -- long quotation -->
231 <!ATTLIST BLOCKQUOTE
232 %attrs; -- %coreattrs, %il8n, %events --
233 cite %URI; #IMPLIED -- URI for source document or msg --
234 >
235 <!------- Inserted/Deleted Text ----->
236 <!ELEMENT (INS|DEL) - - (%flow;)* -- inserted text, deleted text -->
237 <!ATTLIST (INS|DEL)
238 %attrs; -- %coreattrs, %il8n, %events --
239 cite %URI; #IMPLIED -- info on reason for change --
240 datetime %Datetime; #IMPLIED -- date and time of change --
241 >
242 <!------- Lists ----->
243 <!ELEMENT DL - - (DT|DD)+ -- definition list -->
244 <!ATTLIST DL
245 %attrs; -- %coreattrs, %il8n, %events --
246 >
247 <!ELEMENT DT - O (%inline;)* -- definition term -->
248 <!ELEMENT DD - O (%flow;)* -- definition description -->
249 <!ATTLIST (DT|DD)
250 %attrs; -- %coreattrs, %il8n, %events --
251 >
252 <!ELEMENT OL - - (LI)+ -- ordered list -->
253 <!ATTLIST OL
254 %attrs; -- %coreattrs, %il8n, %events --
255 >
256 <!ELEMENT UL - - (LI)+ -- unordered list -->
257 <!ATTLIST UL
258 %attrs; -- %coreattrs, %il8n, %events --
259 >
260 <!ELEMENT LI - O (%flow;)* -- list item -->
261 <!ATTLIST LI

```

```

262 %attrs; -- %coreattrs, %i18n, %events --
263 >
264 <!--===== Forms =====>
265 <!ELEMENT FORM - - (%block;|SCRIPT)+ -(FORM) -- interactive form -->
266 <!ATTLIST FORM
267 %attrs; -- %coreattrs, %i18n, %events --
268 action %URI; #REQUIRED -- server-side form handler --
269 method (GET|POST) GET -- HTTP method used to submit the form--
270 enctype %ContentType; "application/x-www-form-urlencoded"
271 accept %ContentTypes; #IMPLIED -- list of MIME types for file upload --
272 name CDATA #IMPLIED -- name of form for scripting --
273 onsubmit %Script; #IMPLIED -- the form was submitted --
274 onreset %Script; #IMPLIED -- the form was reset --
275 accept-charset %Charsets; #IMPLIED -- list of supported charsets --
276 >
277 <!ELEMENT LABEL - - (%inline;)* -(LABEL) -- form field label text -->
278 <!ATTLIST LABEL
279 %attrs; -- %coreattrs, %i18n, %events --
280 for IDREF #IMPLIED -- matches field ID value --
281 accesskey %Character; #IMPLIED -- accessibility key character --
282 onfocus %Script; #IMPLIED -- the element got the focus --
283 onblur %Script; #IMPLIED -- the element lost the focus --
284 >
285 <!ENTITY % InputType
286 "(TEXT | PASSWORD | CHECKBOX |
287 RADIO | SUBMIT | RESET |
288 FILE | HIDDEN | IMAGE | BUTTON)"
289 >
290 <!ELEMENT INPUT - O EMPTY -- form control -->
291 <!ATTLIST INPUT
292 %attrs; -- %coreattrs, %i18n, %events --
293 type %InputType; TEXT -- what kind of widget is needed --
294 name CDATA #IMPLIED -- submit as part of form --
295 value CDATA #IMPLIED -- Specify for radio buttons and checkbox
es --
296 checked (checked) #IMPLIED -- for radio buttons and check boxes --
297 disabled (disabled) #IMPLIED -- unavailable in this context --
298 readonly (readonly) #IMPLIED -- for text and passwd --
299 size CDATA #IMPLIED -- specific to each type of field --
300 maxlength NUMBER #IMPLIED -- max chars for text fields --
301 src %URI; #IMPLIED -- for fields with images --
302 alt CDATA #IMPLIED -- short description --
303 usemap %URI; #IMPLIED -- use client-side image map --
304 ismap (ismap) #IMPLIED -- use server-side image map --
305 tabindex NUMBER #IMPLIED -- position in tabbing order --
306 accesskey %Character; #IMPLIED -- accessibility key character --
307 onfocus %Script; #IMPLIED -- the element got the focus --
308 onblur %Script; #IMPLIED -- the element lost the focus --
309 onselect %Script; #IMPLIED -- some text was selected --
310 onchange %Script; #IMPLIED -- the element value was changed --
311 accept %ContentTypes; #IMPLIED -- list of MIME types for file upload --
312 %reserved; -- reserved for possible future use --
313 >
314 <!ELEMENT SELECT - - (OPTGROUP|OPTION)+ -- option selector -->
315 <!ATTLIST SELECT
316 %attrs; -- %coreattrs, %i18n, %events --
317 name CDATA #IMPLIED -- field name --
318 size NUMBER #IMPLIED -- rows visible --
319 multiple (multiple) #IMPLIED -- default is single selection --
320 disabled (disabled) #IMPLIED -- unavailable in this context --
321 tabindex NUMBER #IMPLIED -- position in tabbing order --
322 onfocus %Script; #IMPLIED -- the element got the focus --
323 onblur %Script; #IMPLIED -- the element lost the focus --
324 onchange %Script; #IMPLIED -- the element value was changed --
325 %reserved; -- reserved for possible future use --
326 >

```

```

327 <!ELEMENT OPTGROUP - - (OPTION)+ -- option group -->
328 <!ATTLIST OPTGROUP
329 %attrs; -- %coreattrs, %i18n, %events --
330 disabled (disabled) #IMPLIED -- unavailable in this context --
331 label %Text; #REQUIRED -- for use in hierarchical menus --
332 >
333 <!ELEMENT OPTION - O (#PCDATA) -- selectable choice -->
334 <!ATTLIST OPTION
335 %attrs; -- %coreattrs, %i18n, %events --
336 selected (selected) #IMPLIED
337 disabled (disabled) #IMPLIED -- unavailable in this context --
338 label %Text; #IMPLIED -- for use in hierarchical menus --
339 value CDATA #IMPLIED -- defaults to element content --
340 >
341 <!ELEMENT TEXTAREA - - (#PCDATA) -- multi-line text field -->
342 <!ATTLIST TEXTAREA
343 %attrs; -- %coreattrs, %i18n, %events --
344 name CDATA #IMPLIED
345 rows NUMBER #REQUIRED
346 cols NUMBER #REQUIRED
347 disabled (disabled) #IMPLIED -- unavailable in this context --
348 readonly (readonly) #IMPLIED
349 tabindex NUMBER #IMPLIED -- position in tabbing order --
350 accesskey %Character; #IMPLIED -- accessibility key character --
351 onfocus %Script; #IMPLIED -- the element got the focus --
352 onblur %Script; #IMPLIED -- the element lost the focus --
353 onselect %Script; #IMPLIED -- some text was selected --
354 onchange %Script; #IMPLIED -- the element value was changed --
355 %reserved; -- reserved for possible future use --
356 >
357 <!ELEMENT FIELDSET - - (#PCDATA,LEGEND,(%flow;)* -- form control group -->
358 <!ATTLIST FIELDSET
359 %attrs; -- %coreattrs, %i18n, %events --
360 >
361 <!ELEMENT LEGEND - - (%inline;)* -- fieldset legend -->
362 <!ATTLIST LEGEND
363 %attrs; -- %coreattrs, %i18n, %events --
364 accesskey %Character; #IMPLIED -- accessibility key character --
365 >
366 <!ELEMENT BUTTON - -
367 (%flow;)* -(A|formctrl;|FORM|FIELDSET)
368 -- push button -->
369 <!ATTLIST BUTTON
370 %attrs; -- %coreattrs, %i18n, %events --
371 name CDATA #IMPLIED
372 value CDATA #IMPLIED -- sent to server when submitted --
373 type (button|submit|reset) submit -- for use as form button --
374 disabled (disabled) #IMPLIED -- unavailable in this context --
375 tabindex NUMBER #IMPLIED -- position in tabbing order --
376 accesskey %Character; #IMPLIED -- accessibility key character --
377 onfocus %Script; #IMPLIED -- the element got the focus --
378 onblur %Script; #IMPLIED -- the element lost the focus --
379 %reserved; -- reserved for possible future use --
380 >
381 <!--===== Tables =====>
382 <!ENTITY % TFrame "(void|above|below|hsides|lhs|rhs|vsides|box|border)">
383 <!ENTITY % TRules "(none | groups | rows | cols | all)">
384 <!ENTITY % TAlign "(left|center|right)">
385 <!ENTITY % cellhalign
386 "align (left|center|right|justify|char) #IMPLIED
387 char %Character; #IMPLIED -- alignment char, e.g. char=':' --
388 charoff %Length; #IMPLIED -- offset for alignment char --"
389 >
390 <!ENTITY % cellvalign
391 "valign (top|middle|bottom|baseline) #IMPLIED"
392 >

```

```

393 <!ELEMENT TABLE - -
394 (CAPTION?, (COL*|COLGROUP*), THEAD?, TFOOT?, TBODY+)>
395 <!ELEMENT CAPTION - - (%inline;)* -- table caption -->
396 <!ELEMENT THEAD - O (TR)+ -- table header -->
397 <!ELEMENT TFOOT - O (TR)+ -- table footer -->
398 <!ELEMENT TBODY O O (TR)+ -- table body -->
399 <!ELEMENT COLGROUP - O (COL)* -- table column group -->
400 <!ELEMENT COL - O EMPTY -- table column -->
401 <!ELEMENT TR - O (TH|TD)+ -- table row -->
402 <!ELEMENT (TH|TD) - O (%flow;)* -- table header cell, table data cell-->
403 <!ATTLIST TABLE
404 %attrs; -- %coreattrs, %i18n, %events --
405 summary %Text; #IMPLIED -- purpose/structure for speech output--
406 width %Length; #IMPLIED -- table width --
407 border %Pixels; #IMPLIED -- controls frame width around table --
408 frame %TFrame; #IMPLIED -- which parts of frame to render --
409 rules %TRules; #IMPLIED -- rulings between rows and cols --
410 cellpadding %Length; #IMPLIED -- spacing between cells --
411 cellspacing %Length; #IMPLIED -- spacing within cells --
412 %reserved; -- reserved for possible future use --
413 datapagesize CDATA #IMPLIED -- reserved for possible future use --
414 >
415 <!ATTLIST CAPTION
416 %attrs; -- %coreattrs, %i18n, %events --
417 >
418 <!ATTLIST COLGROUP
419 %attrs; -- %coreattrs, %i18n, %events --
420 span NUMBER 1 -- default number of columns in group --
421 width %MultiLength; #IMPLIED -- default width for enclosed COLs --
422 %cellhalign; -- horizontal alignment in cells --
423 %cellvalign; -- vertical alignment in cells --
424 >
425 <!ATTLIST COL
426 %attrs; -- %coreattrs, %i18n, %events --
427 span NUMBER 1 -- COL attributes affect N columns --
428 width %MultiLength; #IMPLIED -- column width specification --
429 %cellhalign; -- horizontal alignment in cells --
430 %cellvalign; -- vertical alignment in cells --
431 >
432 <!ATTLIST (THEAD|TBODY|TFOOT)
433 %attrs; -- %coreattrs, %i18n, %events --
434 %cellhalign; -- horizontal alignment in cells --
435 %cellvalign; -- vertical alignment in cells --
436 >
437 <!ATTLIST TR
438 %attrs; -- %coreattrs, %i18n, %events --
439 %cellhalign; -- horizontal alignment in cells --
440 %cellvalign; -- vertical alignment in cells --
441 >
442 <!ENTITY % Scope "(row|col|rowgroup|colgroup)">
443 <!ATTLIST (TH|TD)
444 %attrs; -- %coreattrs, %i18n, %events --
445 abbr %Text; #IMPLIED -- abbreviation for header cell --
446 axis CDATA #IMPLIED -- comma-separated list of related header
s--
447 headers IDREFS #IMPLIED -- list of id's for header cells --
448 scope %Scope; #IMPLIED -- scope covered by header cells --
449 rowspan NUMBER 1 -- number of rows spanned by cell --
450 colspan NUMBER 1 -- number of cols spanned by cell --
451 %cellhalign; -- horizontal alignment in cells --
452 %cellvalign; -- vertical alignment in cells --
453 >
454 <!--===== Document Head =====>
455 <!ENTITY % head.content "TITLE & BASE?">
456 <!ELEMENT HEAD O O (%head.content;)+(%head.misc;) -- document head -->
457 <!ATTLIST HEAD

```

```

458 %i18n; -- lang, dir --
459 profile %URI; #IMPLIED -- named dictionary of meta info --
460 >
461 <!ELEMENT TITLE - - (#PCDATA) -(%head.misc;) -- document title -->
462 <!ATTLIST TITLE %i18n>
463 <!ELEMENT BASE - O EMPTY -- document base URI -->
464 <!ATTLIST BASE
465 href %URI; #REQUIRED -- URI that acts as base URI --
466 >
467 <!ELEMENT META - O EMPTY -- generic metainformation -->
468 <!ATTLIST META
469 %i18n; -- lang, dir, for use with content --
470 http-equiv NAME #IMPLIED -- HTTP response header name --
471 name NAME #IMPLIED -- metainformation name --
472 content CDATA #REQUIRED -- associated information --
473 scheme CDATA #IMPLIED -- select form of content --
474 >
475 <!ELEMENT STYLE - - %StyleSheet -- style info -->
476 <!ATTLIST STYLE
477 %i18n; -- lang, dir, for use with title --
478 type %ContentType; #REQUIRED -- content type of style language --
479 media %MediaDesc; #IMPLIED -- designed for use with these media --
480 title %Text; #IMPLIED -- advisory title --
481 >
482 <!ELEMENT SCRIPT - - %Script; -- script statements -->
483 <!ATTLIST SCRIPT
484 charset %Charset; #IMPLIED -- char encoding of linked resource --
485 type %ContentType; #REQUIRED -- content type of script language --
486 src %URI; #IMPLIED -- URI for an external script --
487 defer (defer) #IMPLIED -- UA may defer execution of script --
488 event CDATA #IMPLIED -- reserved for possible future use --
489 for %URI; #IMPLIED -- reserved for possible future use --
490 >
491 <!ELEMENT NOSCRIPT - - (%block;)+
492 -- alternate content container for non script-based rendering -->
493 <!ATTLIST NOSCRIPT
494 %attrs; -- %coreattrs, %i18n, %events --
495 >
496 <!--===== Document Structure =====>
497 <!ENTITY % html.content "HEAD, BODY">
498 <!ELEMENT HTML O O (%html.content;) -- document root element -->
499 <!ATTLIST HTML
500 %i18n; -- lang, dir --
501 >

```